

# DAMARK

SHRINK PACKAGING SYSTEMS

## LS-2 SERIES

### Shrink Combo Systems



The LS-2 Combo System combines our SMC 2228 L Bar Sealer and our SZ-24 Shrink Tunnel for ease of ordering. The LSB-2 system comes with a Teflon mesh belt conveyor in the shrink tunnel, which is suited to small or unstable products. The LSR-2 system comes with a live roller conveyor in the shrink tunnel which is suited to flat products longer than 4". Popular options include; casters and a power film unwind with inverting head .

## SPECIFICATIONS

### SMC 2228 Standard Features

- Electrical : 220 volts, 1 ph, 120amp.
- Machine Direction: Standard Infeed Is Right to Left.
- Low Voltage Impulse Sealing System.
- Adjustable, Stainless Steel Product Loading Table.
- Film Clamps.
- Maximum Film Width: 26" Maximum.
- Sealing Area: 22" x 28".
- Quick change roll holder system, fully adjustable for different sized rolls of film.
- Perforator roller for air evacuation from completed package.
- Shipping Size : 80 lg x 49 w x 52 h, 600 lbs

### SZ-24 Standard Features

- Electrical: 220V / 1PH / 48A.
- Shrink Tunnel Chamber: 42" long x 24" wide x 10" high.
- Temperature Controlled by digital temperature controller.
- Adjustable speed conveyor system is either Teflon mesh belt or steel roller type, with the rollers covered in silicone tubing to prevent film sticking to the bare roller. Rollers are set on 2" centers on hollow pin chain. Shipping Size: 73 lg x 51 w x 72 h, 600 lbs. .

### DAMARK SHRINK PACKAGING SYSTEMS

Telephone: 416-609-8011

Fax: 416-298-4328

Email: [info@plexpack.com](mailto:info@plexpack.com)

[www.plexpack.com](http://www.plexpack.com)

**PLEXPACK**



Damark Machinery Distributed By:

